

## **FORMULA 1115 RIG WASH AND HIGH PRESSURE CLEANER**



### **APPLICATIONS**


- F1115 penetrates deep into recesses and crevices of equipment and machinery to chase out soils without disassembling. The resultant run-off will not harm tarmac or asphalt and painted surfaces.
- F1115 has also been used for particularly in high pressure washers. The additive can be used through hot or cold pressure washing machines to penetrate, loosen and flush away hardened grease, dirt and grime.

#### DIRECTIONS FOR USE

- Wet the equipment thoroughly with clean water.
- Apply F1115 solution from the spray lance working upwards. Always test first with a small area for the best dilution rate.



Authorized Distributor



# PRODUCT DATA SHEET

**Excellent Solutions For Reliable Results** 

### **BENEFITS OF FORMULA 1115**

- Remains Stable at High or Low Temperatures can be used with steam cleaners or cold washers. No clogged coils. No un-dissolved particles.
- Powerful, Fast Wetting & Penetration which enables it to remove heavy deposits of oil, dirt and grease from concrete or metal surfaces, vessel bilge decks, engine room and drill floor etc.

F1115 is also used in any pressure washing machine range of mopping. Ideal for use in wherever galleys, cabins, engine rooms, bilges, drill floors etc.

- 100% Soluble in Soft or Hard Water.
- Non-Flammable and Biodegradable.
- No Harsh Fumes in use.
- Non-Corrosive does not attack metal surfaces. Contains no caustic.



### HYSICAL PROPERTIES

Appearance	: Yellow Liquid
Odour	: Pleasant Citrus
рН	: 12 ± 1
Specific gravity	: 1
Flash point	: Not Applicable
Flammability	: Non-Flammable
Viscosity	: Same as Water
Solubility	: Soluble in water
Packing	: 25 litres carboy

- : 209 litres drum
- : 1000 litres IBC tank





No.9, Jalan Pantai Lumut, Kg. Lumut, Belait, KC 3035, Brunei Darussalam Tel: 673-3222538 Fax: 673-322123 Email : info@homansb.com