

# HOT PEPPER

GASTON MILLE



## EN ISO 20345 SAFETY FOOTWEAR

**SB** : Basic requirement (innocuousness, comfort, strength, resistance to shocks hazards & compression 200 J)  
**S1** : SB + closed back + A + E + FO  
**S1P** : S1 + P  
**S2** : S1 + WRU  
**S3** : S2 + P + studded sole

## MARKING

**A** : Antistatic footwear  
**AN** : Ankle protection  
**CI** : Insulation against cold  
**E** : Energy absorption in the heel region  
**ESD** : Electro Static Discharge  
**FO** : Resistance to fuel oil of outsole  
**HI** : Insulation against heat  
**M** : Metatarsal protection  
**P** : Penetration resistance  
**SRA** : Slipping resistance on ceramic tile wet with dilute soap solution  
**SRB** : Slipping resistance on smooth steel with glycerol  
**SRC** = SRA + SRB  
**WR** : Water resistant  
**WRU** : Water resistant upper  
**HRO** : Heat resistant outsole 300°C

Model	Item code	Standard	Marking	EUR Sizes	UK Sizes	US Sizes	Net weight/pair (kg) (42 = men) (38 = ladies)
PEPPER	GPAA3	EN ISO 20345	S3 SRC HI CI	37/48	4/12,5	6/13	1,21
HOT PEPPER	GPHA3	2011	S3 AN HI CI SRC	37/48	4/12,5	6/13	1,29

### SOLE

- Textile antiperforation midsole
- Extra light PU dual density
- High performance grip: SRC

### ENVIRONMENT

- Industry, transport & logistics
- Construction, outdoor

### UPPER

- 200 J composite toe cap
- Very sturdy upper (2-2, 2mm), water & oil resistant
- Micro-ventilated mesh lining: antibacterial
- 100% ventilated & high water-absorbing capacity
- high resistance to abrasion, foot-hygienic proof.

### FOCUS

- Metal free
- Cap protection

Distributed By:



**Address:**  
 Lot 9, Jalan Pantai Perkelahan Kampung Lumut, Seria, KC 3035 Brunei Darussalam

**Contact Information:**  
 Tel: 3222538 Fax: 3221238 E-Mail: info@homansb.com Website: www.homansb.com

